EPA Superfund Record of Decision:

DOVER AIR FORCE BASE EPA ID: DE8570024010 OU 04 DOVER, DE 09/26/1995 Text:

RECORD OF DECISION DECLARATION OF THE SELECTED INTERIM REMEDY

Site Name and Location

Lindane Source Area of Area 6, West Management Unit, Dover Air Force Base, Kent County, Delaware.

Statement of Basis and Purpose

This Record of Decision (ROD) presents the selected interim remedial a for Lindane Source Area, which was chosen in accordance with the requirement the Comprehensive Environmental Response, Compensation, and Liability Act of (CERCLA), as amended by the Superfund Amendments and Reauthorization Act of 1986 (SARA) and, to the extent practicable, the National Oil and Hazardous Substances Pollution Contigency Plan (NCP), 40 CFR Part 300. This decision prepared by the U.S. Air Force, the lead agency, as the owner/operator of th is based on the Administrative Record for the Site. Support was provided by Environmental Protection Agency (EPA) Region III and the Delaware Department of Natural Resources and Environment Control (DNREC).

The State of Delaware and the U.S. Environmental Protection Agency con with the selected interim remedy. The information supporting this interim r action decision is contained in the information repository for the Administr Record located at the Dover Public Library, Dover, Delaware.

Assessment of the Site

The Area 6 Remedial Investigation identified a lindane plume in ground that emanates from the Paint Washout Area (Site SS59). Soil and groundwater indicate that the lindane source resides somewhere between two monitoring we points in this area. Groundwater concentrations of lindane increase from 0. to 27 α g/L between these points. Although a Risk Assessment was not specifi performed for groundwater in the Lindane Source Area, the contribution of li to the overall Area 6 risk from exposure to groundwater under a hypothetical commercial/industrial land use scenario was 2 x 10-5.

Actual or threatened releases of hazardous substances from this Site, addressed by implementing the interim response action selected in this ROD, present a current or potential threat to public health, welfare, or the envi

Lindance Source Area

Description of the Selected Interim Remedy

The selected interim remedy consists of excavation and removal of the contaminated soil source with offsite incineration treatment. The soil sour lindane will be further delineated during the Remedial Design. The lindane-

contaminated soil will be handled as a U129 listed hazardous waste as define the Delaware Regulations Governing Hazardous Waste.

Statutory Determinations

The selected interim remedial action satisfies the remedial selection requirements of CERCLA and the NCP. The selected interim remedy provides th best balance of trade-offs among the nine criteria required to be evaluated CERCLA. The selected interim action provides protection of human health and environment, complies with federal and state requirements that are legally a or relevant and appropriate to the action, and is cost effective. This inte utilizes permanent solutions and alternative treatment technology to the max extent practicable, and satisfies the statutory preference for remedies that treatment that reduces toxicity, mobility, or volume as a principal element. Force understands that although this interim remedy may not achieve MCLs for certain contaminants, this interim action is only part of a total remedial a Base that will be protective of the public health and welfare and of the env when completed (CERLA 121d, 42 U.S.C. 9621.d).

CHARLES T. ROBERTSON, JR. Date Lieutenant General, USAF Air Mobility Command Div Chairperson, Environmental

Protection Committee

THOMAS C. VOLTAGGIO Hazardous Waste Management Division Director Environmental Protection Agency

Date

Region III

Lindance Source Area

RECORD OF DECISION FOR THE INTERIM REMEDY OF LINDANE SOURCE AREA OF AREA 6 WEST MANAGEMENT UNIT DOVER AIR FORCE BASE, DOVER, DELAWARE

August 3, 1995

DECISION SUMMARY FOR THE RECORD OF DECISION LINDANE SOURCE AREA OF AREA 6 WEST MANAGEMENT UNIT DOVER AIR FORCE BASE

INTRODUCTION

Dover Air Force Base (DAFB) recently completed a Focused Feasibility Stud

(FFS) conducted to address chlorinated solvent and pesticide source area contamination in Area 6 of Dover Air Force Base (DAFB), Delaware as an inter response. The FFS was undertaken as part of the U.S. Air Force's Installati Restoration Program (IRP). The basis for the FFS was the Area 6 Remedial Investigation (RI) report dated July 1994, which characterized contamination evaluated potential risks to public health and the environment. The interim performed as the first phase of Feasibility Studies to be conducted on sites Management Unit, the management unit to which Area 6 belongs. The scope of FFS was limited to the evaluation of alternatives for remediation of primary chlorinated solvent and pesticide source areas orginating in the northern, u portion of the Area 6 region of investation. The final remediation of source if necessary, and non-source area contamination in Area 6 posing human healt environmental risks will be addressed in the final Base-wide Feasibility Stu

This Record of Decision (ROD) addresses the lindane source area, which one of the source areas evaluated in the FFS. This ROD summarizes the FFS, describes the remedial alternatives that were evaluated, identifies the reme alternative selected by DAFB, and explains the reasons for this selection. Environmental Protection Agency (EPA) and the State of Delaware concur with interim remedy selected in this ROD.

As an aid to the reader, a glossary of the technical terms used in thi provided at the end of the summay.

Lindance Source Area

PUBLIC PARTICIPATION

The Proposed Plan for this site was issued on June 16, 1995. The publ

comment period on the Plan was open through July 31, 1995. Documents compri the Administrative Record for the site were available at the Dover Public Li SITE BACKGROUND

DAFB is located in Kent County, Delaware, 3.5 miles southeast of the c Dover (Figure 1) and is bounded to the southwest by the St. Jones River. DA comprises approximately 4,000 acres of land, including annexes, easements, a property (Figure 2). The surrounding area is primarily cropland and wetland

DAFB began operation in December 1941. Since then, various military s have operated out of DAFB. The present host organization is the 436th Airli Its mission is to provide global airlift capability, including transport of equipment, and relief supplies.

DAFB is the U.S. East Coast home terminal for the C-5 Galaxy aircraft. Base also serves as the joint services port mortuary, designed to accept cas the event of war. The C-5 Galaxy, a cargo transport plane, is the largest a the USAF, and DAFB is one of a few military bases at which hangars and runwa designed to accommodate these planes.

The portion of DAFB addressed in this ROD is located within Area 6 of West Management Unit. The West Management Unit is one of four Management Units into which the Base has been divided (Figure 3). Area 6 is the larges associated areas identified in the West Management Unit. The Area 6 region investigation extends approximately 8,400 feet from its northern most point hardstand and Building 723 to its southern most point near the St. Jones Riv (Figure 4). The area north of U.S. Highway 113 contains the industrialized of the Area 6 region of investigation. The location addressed in this ROD f this industrialized portion of Area 6.

Lindance Source Area

DAFB is relatively flat, with elevations ranging from approximately 10 feet above mean sea level (MSL). The ground surface is covered almost entir buildings, concrete, and asphalt. Surface water runoff throughout the indus portion of Area 6 is controlled by an extensive storm drainage system. The drains direct most runoff to either Pipe Elm Branch or the golf course tribu St. Jones River.

The Columbia Formation is the shallowest water-bearing unit and holds water table aquifer. The Columbia Formation typically consists of fine to c grained sand with varying amounts of silt, clay, and gravel. Discontinuous gravel, silt and clay are also common. Generally, the upper portion of the Formation is finer grained and contains more silt and clay lenses than the d portion. The water able is generally encountered at a depth of 10 to 12 fee ground surface (bgs) in the northern portion of Area 6 and shallows to within feet of the surface in the Base housing area near the St. Jones River. The groundwater elevation or potentiometric surface of both the shallow and deep of the Columbia Aquifer range from approximately 13.5 feet MSL in the northe

portion to less than 3 feet MSL near the St. Jones River. The thickness of Columbia Formation in Area 6 ranges from 28 to 64 feet.

Unconformably underlying the Columbia Formation is the upper unit of t Calvert Formation, which generally consists of gray to dark gray firm, dense clay, with thin laminations of silt and fine sand. This upper silt and clay in thickness from 15 to 21 feet in the northern portion of Area 6. The hydr conductivity of this unit range from 6.83 x 10-3 to 1.53 x 19-3 ft/day (2.41 x 10-7 cm/sec), which are three to five orders of magnitude lower than the o Columbia Formation. These significantly lower hydraulic conductivities form to the vertical migration of constituents identified in the Columbia Aquifer Underlying this confining unit is the upper sand unit of the Calvert Formati Frederica Aquifer. This aquifer averages 22 feet in thickness in the vicini No constituents of concern were identified in the three Frederica monitoring

Lindance Source Area

installed in Area 6. Additionally, no production wells are installed the Fr Aquifer in the vicinity of DAFB.

Area 6 is defined by the association of chlorinated solvents in ground forming a plume in the Columbia Aquifer. The Area 6 RI identified a lindane groundwater plume (Figure 5) that emanates from the Paint Washout Area (Site SS59). Lindane is a nonvolatile pesticide compound. The lindane source is to reside in the subsurface soils of the open storage yard in the Paint Wash near well MW212S. Lindane concentrations in shallow groundwater are approxi three orders of magnitude higher in this well than in the nearest upgradient well.

SOURCE AREA CHARACTERISTICS

The following section describes the physical and chemical characterist lindane source area, which is addressed in this Record of Decision.

Soil and groundwater data indicate that a lindane source area resides Paint Washout Area (Site SS59), located in the eastern portion of the open s yard near 5th Street. A map of the Paint Washout Area vicinity summarizing available lindane data in soil and groundwater is presented in Figure 6. As the figure, the concentration of lindane in the groundwater between wells 21 212S increases from 0.042 æg/L to 27 æg/L between these point. Thus, the groundwater data indicates that the soil-based lindane source resides in the well 212S. For cost estimating purposes only, the assumed dimensions of the source area are 20 feet by 20 feet by 1 foot thick, covered by 1 foot of soi remedial design will define the exact dimensions of the lindane source area.

SUMMARY OF SITE RISKS

The full Risk Assessment (RA) for Area 6 can be found in the final Are report dated July 1994. The purpose of the RA is to determine whether expos site-related contaminants could adversely affect human health and the environment focus of the baseline RA is on the possible human health and environment

Lindance Source Area

effects that could occur under current or potential future use conditions in that the contamination is not remediated. The risk is pressed as lifetime e cancer risk (LECR) for carcinogens, and hazard quotient (HQ) for noncarcinog For example, an LECR of 1 x 10-6 represents one additional case of cancer in million exposed population, whereas a hazard quotient above one presents a 1 of noncarcinogenic health effects in exposed populations.

The baseline RA focused on potential pathways by which maintenance and construction workers would be exposed to contaminated materials in Area 6. workers' exposure to groundwater and soil have been evaluated under a regula maintenance scenario; a future construction scenario; and a hypothetical fut groundwater use from the Columbia Aquifer under a commercial/industrial scen Although a specific Lindane Source Area RA has not been performed, the calcurisk contribution from the hypothetical future exposure to lindane-contamina groundwater in Area 6 was 2 x 10-5. In addition to the overall Area 6 risk, concentrations in the Lindane Source Area have been compared to the risk-bas screening concentrations (RBSCs) developed for commercial/industrial scenarion DAFB to identify if it presents a risk-based concern.

The future use of groundwater from the Columbia Aquifer by Base personnel is quite unlikely and hypothetical. This hypothetical future groundwater us that groundwater from the Columbia Aquifer will be used for drinking and sho purposes by Base personnel under a commercial/industrial scenario. The RBSC compared with maximum detected concentration of lindane in the Lindane Sourc Area. The maximum detected lindane concentration of 27 æg/L in Lindane Sour Area groundwater is higher than its RBSC of 0.22 æg/L.

The maximum concentration of lindane detected in soil was compared to its RBSC developed for exposure to soil under a commercial/industrial scenario.

Lindance Source Area

The groundwater and soil data suggest that there is a soil-based sou lindane, and the possibility exists for exposure of workers to hazadous subs soil during excavation activities. Source areas identified during excavatio worker protection in accordance with heath and safety protocols. All worker performing excavation work at DAFB will be health and safety trained for wor CERCLA sites.

Based on the direction of groundwater flow, the Area 6 plume extends i southerly direction towards the St. Jones River. There are no surface water points within Area 6 between the Lindane Source Area and the river. Present Area 6 plume is confined within the Base property, and has not reached the S River.

Actual or threatened releases of hazardous substances from this Site, addressed by the selected alternative or one of the other active measures co may present a current or potential threat to public health, welfare, or the

REMEDIAL ACTION OBJECTIVE

For the lindane source area, an action-specific interim RAO of removing soil source of lindane has been established, though no specific lindane conc limits have been set. A lindane action level will be established during the Design that will minimize further degradation of groundwater quality through The action level will be determined through the use of an appropriate leachi

and collection of site data. Remediation of the plume itself is not address ROD.

The issues of final cleanup levels and attainment of ARARs will be add in the Final Basewide Record of Decision. The remedial action selected for is only part of the remedial action which will be selected in a Final Basewi

SUMMARY OF ALTERNATIVES

Engineering technologies applicable to remediating the contaminated me were screened according to their effectiveness and implementability. Only o

Lindance Source Area

technology was determined to be applicable and it was developed into the act remedial alternatives. The two remedial alternatives evaluated are presente

Alternative 1-No Action.

Alternative 2-Offsite Incineration of Lindane-Contaminated Soil.

The two remedial alternatives that were evaluated in detail are desc below. In addition, the capital, annual operation and maintenance (O&M), an present worth costs of both alternatives are provided.

Alternative 1

Lindane Source Area

Capital Cost \$000

Annual O&M Cost \$000

Present Worth \$000

The no action alternative is evaluated in order to establish a baselin

comparison against other alternatives. Under this alternative, no efforts a undertaken to remove the lindane-contaminated soil source of the lindane groundwater plume.

Alternative 2

Lindane Source Area

Capital Cost \$140,000

Annual O&M Cost \$000

Present Worth \$140,000

Alternative 2 consists of excavation and removal of the lindane-contam soil source with offsite incineration treatment.

Lindance Source Area

The soil source of lindane contamination will be further delineated du remedial design. The lindane contaminated soil is interpreted as a U129 lis hazardous waste under the implementing regulations of the Resource Conservat and Recovery Act (RCRA), and as such is subject to land disposal restriction Therefore, lindane-contaminated soil exceeding action levels will be excavat sent to an offsite RCRA-permitted facility for incineration and disposal. T treatment method will reduce residual lindane concentrations in the treated below the treatment level required for disposal of the soil.

The action-specific RAO of removing the soil-based source of lindane w achieved within one year. The present worth cost of this alternative is \$14

EVALUATION OF ALTERNATIVES

The selected alternative for remediating the contamination in the Lindane Source Area is Alternative 2. Based on current information, this alternative the best balance of trade-offs among the alternatives with respect to the nithat are required to be evaluated under CERCLA. This section profiles the performance of the selected alternative against the nine criteria and explait compares to the other alternative under consideration.

Overall Protection of Human Health and the Environment

The overall protectiveness criterion is a composite of other evaluatio especially short-term effectiveness, long-term effectiveness, and compliance ARARS. Alternative 1 (no action) is not considered effective because the s of lindane contamination will remain in place. Alternative 2 (lindane remov meet the RAO and is considered effective.

Compliance With ARARs

There are no ARAR considerations associated with Alternative 1 (no act Alternative 2 (lindane removal) consist of the excavation and removal of the based source of lindane. This soil will be managed as U129 listed hazardous The excavation, handling, transportation, treatment, and ultimate disposal a

Lindance Source Area

this soil will comply with RCRA requirements. The Delaware regulations implementing RCRA in the state are the Delaware Regulations Governing Hazard Waste (DRGHW). Lindane is listed as a hazardous waste under DRGHW 261.33. The storage of hazardous waste in piles is addressed under DRGHW 264. The transportation of hazardous waste is addressed under DRGHW Part 263. Finall disposal restrictions are addressed under DRGHW Part 268.

Long-Term Effectiveness and Permanence

The long-term effectiveness and permanence criterion primarily conside magnitude of residual risk that would remain after the implementation of an alternative, and the adequacy and reliability of the controls instituted. U Alternative 1 (no action), the lindane-contaminated soil source will be left Hence, the long-term protectiveness of this alternative cannot be demonstrat

Alternative 2 (lindane removal) provides for the removal and treatment lindane-contaminated soil source material. This represents a permanent reme will halt further leaching of lindane into groundwater.

Reduction of Toxicity, Mobility, and Volume

No reduction of toxicity, mobility, or volume will be achieved from th implementation of Alternative 1. Alternative 2 consists of the removal and incineration of the lindane-contaminated woil, which will reduce the toxicit treated soil. In addition, it will reduce the source of lindane contaminati leach into groundwater.

Short-Term Effectiveness

Alternative 1 (no action) includes no remedial actions. Therefore, the be no short-term impacts on community or worker health or the environment from construction activities. However, Alternative 1 will not eliminate the soil of lindane.

Alternative 2 will result in the rapid removal of the soil-based sourc lindane. The exposure by construction workers to lindane-contaminated soil

Lindance Source Area

will be minimized through the use of appropriate protective clothing and equ
No impacts to the community are anticipated.

Implementability

Three main factors are considered under this criterion: technical feasib administrative feasibility, and availability of services and materials. Bot are administratively feasible and the required services and materials are re available. Hence, the comparison will focus on the technical feasibility of alternatives.

Alternative 1 (no action) have no technical feasibility considerations technical feasibility considerations associated with Alternative 2 (lindane minimal. The qualified excavation and transportation contractors required to the work are readily available. In addition, there is ample offsite inciner available to perform the required thermal destruction.

Cost

No direct costs are associated with the implementation of Alternative 1 (action). The capital costs of Alternative 2 (lindane removal) is \$140,000.

no O&M costs associated with either alternative.

State Acceptance

The State of Delaware concurs with the selected interim remedy for t source area.

Community Acceptance

No public comments were received on the proposed interim remedy.

CONCLUSION

Based on the evaluation of the alternatives using the nine criteria, A 2 (lindane removal) is preferred. Alternative 2 is protective of human heal environment, complies with all ARARs, and represents a permanent remedy that protect groundwater quality.

Lindance Source Area

The selected alternative utilizes permanent solutions and alternative technologies to the maximum extent practicable. This interim action will no negatively impact the ability to implement a final action if required. The will be selected in the final Base-wide ROD.

Actual or threatened releases of hazardous substances from this Site, if addressed by the selected alternative, may present a current or potential th public health, welfare, or the environment.

Lindance Source Area

GLOSSARY AND ACRONYMS

Aquifer - A geologic formation capable of yielding water to wells and spring

ARARS - Applicable or Relevant and Appropriate Requirements. Criteria set f
by federal and state statute and regulations that must be considered in t
evaluation of remedial alternatives.

Capital Cost - Cost incurred for the construction and startup of a facility.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability

Act. Federal law creating the Superfund program.

DAFB - Dover Air Force Base.

EPA - Environmental Protection Agency.

FS - Feasibility Study.

FFS - Focused Feasibility Study.

Groundwater - Subsurface water residing in a zone of saturation.

HQ - Hazard Quotient. An indicator of the noncarcinogenic health risk assoc with exposure to a chemical.

Incineration - The process of burning a material so that only ashes remain.

Leach - The solubilization and transport of constituents in soil through the of surface water to groundwater.

LECR - Lifetime Excess Cancer Risk. The probability of the carcinogenic hea associated with exposure to chemicals of concern.

O&M Cost - Annual cost incurred for operation and maintenance of a facility.

Plume - A recognizable distribution of constituents in groundwater.

Potentiometric Surface - An imaginary surface that represents the static hea groundwater and is defined by the level to which water will rise.

Lindance Source Area

GLOSSARY (cont'd)

- RAO Remedial Action Objective. Cleanup goal established for the remediati
- RBSC Risk-Based Screening Concentration. A chemical-specific concentratio to preliminarily assess whether exposure to the chemical poses a poten health risk.
- RCRA Resource Conservation and Recovery Act.
- ROD Record of Decision. A legal document issued by the lead governmental agency selecting the remedy to be implemented at a CERCLA site.

Lindance Source Area